

THREE PHASE ENERGY METER MID APPROVED

THREE PHASE ENERGY METER DIRECT CONNECTION - RS485 MOD. PRO380

THREE PHASE ENERGY METER WITH EXTERNAL CTs - RS485 MOD. PRO380-S CT



Available measure : Current, Voltage, Active, Reactive and Apparent Power, Total and Bidirectional Energy, Freq. , Power Factor, Totalizer for energy bidirectional power measurement, SO pulse output.

	PRO380 DC MOD	PRO380-S CT MOD
DIMENSIONS	140x63x70 mm	
MOUNTING	DIN Rail	
ACCURACY	COMPLY TO EN50470-3	
ACTIVE ENERGY	+/- 1 %	
MINIMUM CURRENT	0,05 Ib	
BASE CURRENT (Ib)	5 A	1,5 A
MAX CURRENT (Imax)	100 A	6 A

THE MID DIRECTIVE - Transposed at national level with the Italian Legislative Decree 22/2007 is a new approach directives adopted by the European community. The objective of this approach is the definition of shared and common technical rules which allow instruments to move freely within the community. The instruments covered by this standard bear the the CE marking, and it is important emphasise thate **the directive relates exclusively to the design and production of measuring instruments.**



scan the qrcode
TO DISCOVER MORE

